



Shaffer
ENERGIZING TOMORROW

LED 1 X 4 Panel



< Features

Electrical Parameters	
Input Voltage	140-270V AC
Wattage	36 W 40W
Driver Efficiency	>90
Power Factor	>095
Total Harmonic Distortion	<10
Over Voltage Protection	Provided
Optical Parameters	
Colour Temperature	3000-6000K
CRI	>80
LED Life with L70 Criteria	>50000 Hours
Optics	Closed, Diffuser
Efficacy	>100 Lumen/Watt
General Parameters	
Housing	Aluminium
Operating Temperature Range	-10 to 50 degree centigrade
Off State Power	Zero
Mounting	Recessed/Surface Mount/Pendent
Finish	White/Silver
Certification	CE
Environment	IP-20

< Benefits

- Sustainable and Asthetically Designed.
- Suitable replacement of conventional 1x4 fittings.
- Available with Dimmable option.
- Available in Cool White Color suitable for office lighting.
- Appropriate Unify Glare Ratio.
- Use of premium grade alloys for enhanced thermal conduction.
- High quality diffuser is used for secondary optics.
- Easy Ballast mounting with Velcro.
- Also Available in Troffer.

Typical Applications Include:

- Office Lighting.
- Common Area Lighting.
- Hospital & Wellness Lighting.



PRODUCT ORDERING INFORMATION

Product Code	Product	CCT	Wattage
SH 1X4 36/40W CW/WW REC/SRF/PND WH	LED 1X4 Panel	Cool White/Warm White	36W 40W

Asia Pacific • Africa • Middle East • Europe
Specifications are typical values and may change without notification.
Copyright © Shaffer Energy. 2018 All rights reserved.