



## < Benefits

- Sustainable and Aesthetically Designed.
- Available in Cool White Color suitable for T8 & T10 FTL lamp replacement.
- More than 50% Energy saving.
- High quality diffuser is used for secondary optics.
- Special Thermal pad back of PCB for good heat distribution.
- Environmentally friendly - contains no mercury or other hazardous materials.
- Batten luminaire for single or continuous row mounting

### Typical Applications Include:

- Indoor Lighting
- Cove Lighting
- Hospitality
- Commercial Lighting
- Industrial Lighting

## < Features

Electrical Parameters	
Input Voltage	140-270V AC
Size	600mm 1200mm
Wattage	9W 18/20/22W
Driver Efficiency	>90
Power Factor	>0.95
Optical Parameters	
Colour Temperature	3000-6500K
CRI	>80
LED Life with L70 Criteria	>50000 Hours
Optics	Milky Diffuser, Closed
Lumen Efficacy	>110 Lm/Watt
General Parameters	
Operating Temperature Range	-10 to 50 degree centigrade
Housing	Aluminium/Polycarbonate with Milky Diffuser
Mounting	Wall Mount/Surface Mount
Off State Power	Zero
Certification	CE
Environment	IP-20



## PRODUCT ORDERING INFORMATION

Product Code	Product	CCT	Wattage
SH BT 9/18/20/22W CW WH	LED Batten Light	Cool White/Warm White	9W 18W 20W 22W

Asia Pacific • Africa • Middle East • Europe  
 Specifications are typical values and may change without notification.  
 Copyright © Shaffer Energy. 2018 All rights reserved.