



< Benefits

- Sustainable and Asthetically Designed.
- Reliable and uniform asymmetric light.
- Works as excellent accent light with uniform beam control.
- Available in Cool White Color suitable for various requirement.
- Environment friendly, no mercury, no ultra violet and infra red radiation.
- Integrated Driver for easy installation.
- Use of premium grade alloys for enhanced thermal conduction.

Typical Applications Include:

- Industries
- Parking Lots
- Gallery
- Railway Yards

< Features

Electrical Parameters

Input Voltage	140-277V AC
Frequency	50Hz
Wattage	10 W
Driver Efficiency	>90
Power Factor	>0.95
Open Circuit Protection	Provided
Short Circuit Protection	Provided
Driver	Integrated Driver

Optical Parameters

Colour Temperature	5500-6500K
CRI	>80
LED Life with L70 Criteria	>35000 Hours
Optics	Diffuser, Closed
Optic Cover	Poly Carbonate Diffuser
Efficacy	>100 Lumen/Watt

General Parameters

Operating Temperature Range	-5 to 50 degree centigrade
Housing	Pressure Die Cast Aluminium
Off State Power	Zero
Certification	CE
Environment	IP-65



PRODUCT ORDERING INFORMATION

Product Code	Product	Colour Temp.	Wattage
SH BH 10W CW GR	LED Bulk Head	CW	10W

Asia Pacific • Africa • Middle East • Europe
Specifications are typical values and may change without notification.
Copyright © Shaffer Energy. 2018 All rights reserved.