



< Benefits

- Sustainable and Aesthetically Designed.
- Suitable replacement of CFL downlighters.
- Available with Dimmable option.
- Available in Cool White Color suitable for office lighting.
- Appropriate Unify Glare Ratio.
- Use of premium grade alloys for enhanced thermal conduction.
- High quality diffuser is used for secondary optics.
- Easy Ballast mounting

Typical Applications Include:

- Office Lighting.
- Corridors.
- Common Area Lighting.
- Hospital & Wellness Lighting.

< Features

Electrical Parameters

Input Voltage	140-270V AC
Wattage	6W 12W 16W 24W 30W
Driver Efficiency	>90
Total Harmonic Distortion	<10
Over Voltage Protection	Provided

Optical Parameters

Colour Temperature	3000-6000K
CRI	>80
LED Life with L70 Criteria	>50000 Hours
Beam Angle	Narrow/Wide
Optics	Reflector

General Parameters

Operating Temperature Range	-10 to 50 degree centigrade
Housing	Pressure Die Cast Aluminum
Off State Power	Zero
Certification	CE
Environment	IP-20



PRODUCT ORDERING INFORMATION

Product Code	Product	CCT	Wattage
SH CDL 6/12/16/24/30W CW/WW REC WH	LED COB Downlighter	Cool White/Warm White	6W 12W 16W 24W 30W

Asia Pacific • Africa • Middle East • Europe
Specifications are typical values and may change without notification.
Copyright © Shaffer Energy. 2018 All rights reserved.