



Shaffer
ENERGIZING TOMORROW



LED Industrial Fitting

< Benefits

- Sustainable and Aesthetically Designed.
- Available in Cool White Color suitable for T8 & T10 FTL lamp replacement.
- More than 50% Energy saving.
- High quality diffuser is used for secondary optics.
- Special Thermal pad back of PCB for good heat distribution.
- Environmentally friendly - contains no mercury or other hazardous materials.
- Meet LM-79 & EN 62471-1 photoelectricity testing.

Typical Applications Include:

- Indoor Lighting.
- Commercial Lighting.
- Industrial Lighting.

< Features

Electrical Parameters	
Input Voltage	140-270V AC
Size	Suitable for 2X18W
Lamp Wattage	2X18W
Driver Efficiency	>85
Fixture Wattage	36W
Power Factor	>0.9
Optical Parameters	
Colour Temperature	3000-6000K
CRI	>80
LED Life with L70 Criteria	>35000 Hours
Optics	Diffuser, Closed
Optics	Reflector
General Parameters	
Operating Temperature Range	-5 to 50 degree centigrade
Housing	ABS/Plastic
Certification	CE
Environment	Weatherproof



PRODUCT ORDERING INFORMATION

Product Code	Product	Colour Temp.	Wattage
SH IB 2X18W CW SRF/PND WH	LED Industrial Fitting	CW	36W

Asia Pacific • Africa • Middle East • Europe
Specifications are typical values and may change without notification.
Copyright © Shaffer Energy. 2018 All rights reserved.