



Benefits

- Pathway Light.
- Inground Application.
- Holistic Thermal Design.
- Unique Sleek Design
- Environmental Friendly- contains no mercury or other hazardous materials.
- Use of premium grade alloys for enhanced thermal conduction.
- Visibility from more than 300 Meters

Typical Applications Include:

- Pathways
- Galleries
- Roadway
- Garden

Features

Electrical Parameters	
Input	140-277V AC
Frequency	50Hz
Driver Efficiency	>85%
Fixture Wattage	2x3W 3X3W 4X3W
Power Factor	>0.9
Over Voltage Protection	Provided
Optical Parameters	
Colour	WW/CW
CRI	>80
LED Life with L70 Criteria	>50000 Hours
Optics	Reflector/Lens
Flashing of LEDs	Yes
General Parameters	
Housing	Aluminum Alloy
Cover	Polycarbonate/Glass
Operating Temperature Range	-10 to 55 degree centigrade
Environment	IP-67/68 Protected



PRODUCT ORDERING INFORMATION

Product Code	Product	Colour Temp.	Wattage
SH PWL 06/09/12W CW/WW IP67/68	LED Pathway Light	CW/WW	06W 09W 12W

Asia Pacific • Africa • Middle East • Europe
 Specifications are typical values and may change without notification.
 Copyright © Shaffer Energy. 2018 All rights reserved.