



Shaffer
ENERGIZING TOMORROW



< Benefits

- Sustainable and Aesthetically Designed.
- Available in Cool White Color suitable for 4 Pin CFL replacement.
- More than 60% Energy saving.
- High quality diffuser is used for secondary optics.
- Special Thermal pad back of PCB for good heat distribution.
- Environmentally friendly - contains no mercury or other hazardous materials.
- Meet LM-79 & EN 62471-1 photoelectricity testing.

Typical Applications Include:

- Indoor Lighting.
- Commercial Lighting.
- Corridors

LED PL Light

< Features

Electrical Parameters	
Input Voltage	140-270V AC
Size	210mm 416 mm
Wattage	9W 18W
Driver Efficiency	>90
Power Factor	>0.95
Socket	2G11
Optical Parameters	
Colour Temperature	WW/CW
CRI	>80
LED Life with L70 Criteria	>50000 Hours
Efficacy	>100 Lm/Watt
General Parameters	
Operating Temperature Range	-10 to 50 degree centigrade
Housing	Aluminium with milky diffuser
Off State Power	Zero
Certification	CE
Environment	IP-20



PRODUCT ORDERING INFORMATION

Product Code	Product	CCT	Wattage
SH PL 09/18W CW	LED PL Light	Cool White/Warm White	9W 18W

Asia Pacific • Africa • Middle East • Europe
Specifications are typical values and may change without notification.
Copyright © Shaffer Energy. 2018 All rights reserved.