



Shaffer
ENERGIZING TOMORROW

LED Projection Light



< Features

Electrical Parameters	
Input Voltage	140-270V AC
Wattage	15W 30W
Driver Efficiency	>90
Power Factor	>0.95
Total Harmonic Distortion	<15
Over Voltage Protection	Provided
Optical Parameters	
Colour Temperature	2700-6000K
CRI	>85
LED Life with L70 Criteria	>50000 Hours
Optics	High quality lens
Lumen Output	>90 Lm/Watt
General Parameters	
Operating Temperature Range	-10 to 50 degree centi-grade
Housing	Pressure Die Cast Aluminum
Finish	White/Black
Control Gear	Integral/External
Dimmable	Yes
Adjustable Lens	Yes
Off State Power	Zero
Certification	CE
Environment	IP-20

< Benefits

- Sustainable and Asthetically Designed.
- Suitable replacement of Halogen Projection Light
- Works as excellent accent light with uniform beam control
- Available in Cool White, Warm White and Neutral White Color suitable for various requirement
- Appropriate Unify Glare Ratio.
- Use of premium grade alloys for enhanced thermal conduction.

Typical Applications Include:

- Track Light
- Galleries
- Musuems
- Art Galley
- Showrooms



PRODUCT ORDERING INFORMATION

Product Code	Product	CCT	Wattage
SH FPL 15/30W CW/WW TR/SRF WH/BLK	LED Projection Light	Cool White/Warm White	15W 30W

Asia Pacific • Africa • Middle East • Europe
Specifications are typical values and may change without notification.
Copyright © Shaffer Energy. 2018 All rights reserved.