



< Benefits

- Sustainable and Asthetically Designed.
- Suitable replacement of CFL downlighters.
- Available with Dimmable option.
- Available in Cool White Color suitable for office lighting.
- Appropriate Unify Glare Ratio.
- Use of premium grade alloys for enhanced thermal conduction.
- High quality diffuser is used for secondary optics.
- Easy Ballast mounting

Typical Applications Include:

- Office Lighting.
- Common Area Lighting.
- Hospital & Wellness Lighting.

< Features

Electrical Parameters

Input Voltage	140-277V AC
Wattage	3W 6W 12W 15W 18W
Driver Efficiency	>85
Total Harmonic Distortion	<15
Over Voltage Protection	Provided

Optical Parameters

Colour Temperature	3000-6000K
CRI	>80
LED Life with L70 Criteria	>50000 Hours
Optics	Closed Milky Diffuser

General Parameters

Housing	Pressure Die Cast Aluminium
Operating Temperature Range	-10 to 50 degree centigrade
Off State Power	Zero
Housing	Pressure Die Cast Aluminium
Finish	White
Certification	CE
Environment	IP-20



PRODUCT ORDERING INFORMATION

Product Code	Product	CCT	Wattage
SH SP 3/6/12/15/18W CW/WW REC/SRF WH	LED Slim Panel	Cool White/Warm White	3W 6W 12W 15W 18W

Asia Pacific • Africa • Middle East • Europe
Specifications are typical values and may change without notification.
Copyright © Shaffer Energy. 2018 All rights reserved.