



**Shaffer**  
ENERGIZING TOMORROW



## < Benefits

- Sustainable and Aesthetically Designed.
- Reliable and uniform asymmetric light.
- Works as excellent accent light with uniform beam control.
- Available in Cool White, Warm White and Neutral White Color suitable for various requirement
- Appropriate Unify Glare Ratio.
- Use of premium grade alloys for enhanced thermal conduction.
- Integrated driver makes sure installation is simple.

Typical Applications Include:

- Stairs
- Steps
- Gallery

# LED Step Light

## < Features

Electrical Parameters	
Input Voltage	140-280V AC
Frequency	50-60Hz
Wattage	5W
Driver Efficiency	>90
Power Factor	>0.95
Driver	Integrated Driver
Optical Parameters	
Colour Temperature	3000-6500K
CRI	>80
LED Life with L70 Criteria	>35000 Hours
Optics	Diffuser, Closed
Optic Cover	Poly Carbonate Diffuser
General Parameters	
Operating Temperature Range	-5 to 50 degree centi-grade
Housing	Pressure Die Cast Aluminium
Off State Power	Zero
Installation	Recessed
Certification	CE
Environment	IP-65



## PRODUCT ORDERING INFORMATION

Product Code	Product	Colour Temp.	Wattage
SH STEP M1 5W CW/WW	LED STEP LIGHT	CW/WW	5W

Asia Pacific • Africa • Middle East • Europe  
Specifications are typical values and may change without notification.  
Copyright © Shaffer Energy. 2018 All rights reserved.