



Shaffer
ENERGIZING TOMORROW



LED Surface Panel

< Features

Electrical Parameters	
Input Voltage	140-270V AC
Wattage	6W 12W 18W 20W 24W
Driver Efficiency	>90
Total Harmonic Distortion	<10
Over Voltage Protection	Provided
Optical Parameters	
Colour Temperature	3000-6000K
CRI	>80
LED Life with L70 Criteria	>35000 Hours
Optics	Milky Diffuser
General Parameters	
Operating Temperature Range	-10 to 50 degree centi-grade
Housing	Pressure Die Cast Aluminium
Mounting	Surface Mount
Off State Power	Zero
Certification	CE
Environment	IP-20

< Benefits

- Sustainable and Aesthetically Designed.
- Suitable replacement of CFL downlighters.
- Available in Cool White Color suitable for office lighting.
- Appropriate Unify Glare Ratio.
- Use of premium grade alloys for enhanced thermal conduction.
- High quality diffuser is used for secondary optics.
- Easy Ballast mounting

Typical Applications Include:

- Office Lighting
- Corridors
- Common Area Lighting
- Hospital & Wellness Lighting



PRODUCT ORDERING INFORMATION

Product Code	Product	CCT	Wattage
SH SP 06/12/18/20/24W CW/WW SRF WH	LED Surface Panel	Cool White/Warm White	6W 12W 18W 20W 24

Asia Pacific • Africa • Middle East • Europe
Specifications are typical values and may change without notification.
Copyright © Shaffer Energy. 2018 All rights reserved.