



Shaffer
ENERGIZING TOMORROW

LED Troffer 2 X 2



< Benefits

- Sustainable and Aesthetically Designed.
- Suitable replacement of conventional 2x2 panels.
- Available with Dimmable option.
- Available in Cool White Color suitable for office lighting.
- Appropriate Unify Glare Ratio.
- Use of premium grade alloys for enhanced thermal conduction.
- High quality diffuser is used for secondary optics.
- Easy Ballast mounting with Velcro.

Typical Applications Include:

- Office Lighting.
- Common Area Lighting.
- Hospital & Wellness Lighting.

< Features

Electrical Parameters	
Input Voltage	140-270V AC
Wattage	36 W 45W 55W
Driver Efficiency	>90
Power Factor	>0.95
Total Harmonic Distortion	<10
Over Voltage Protection	Provided
Optical Parameters	
Colour Temperature	3000-6000K
CRI	>80
LED Life with L70 Criteria	>35000 Hours
Optics	Closed, Diffuser
LED (Nichia)	>110 Lumen/Watt
General Parameters	
Housing	CRCA/Aluminium
Operating Temperature Range	-10 to 50 degree centi-grade
Off State Power	Zero
Mounting	Recessed/Surface Mount
Certification	CE
Environment	IP-20



PRODUCT ORDERING INFORMATION

Product Code	Product	CCT	Wattage
SH 2X2 36/45/55W CW/WW REC/SRF WH	LED 2X2 Troffer	Cool White/Warm White	36W 45W 55W

Asia Pacific • Africa • Middle East • Europe
Specifications are typical values and may change without notification.
Copyright © Shaffer Energy. 2018 All rights reserved.