



## < Benefits

- Sustainable and Aesthetically Designed.
- Available in Cool White Color suitable for T8 & T10 FTL lamp replacement.
- More than 50% Energy saving.
- High quality diffuser is used for secondary optics.
- Special Thermal pad back of PCB for good heat distribution.
- Environmentally friendly - contains no mercury or other hazardous materials.
- Meet LM-79 & EN 62471-1 photoelectricity testing.

### Typical Applications Include:

- Home
- Offices
- Hospitals
- Hotels

## < Features

### Electrical Parameters

Input Voltage	140-270V AC
Size	2 Feet    4 Feet
Wattage	9W        18/20W
Driver Efficiency	>90
Power Factor	>0.95
End Cap	G13 Base

### Optical Parameters

Colour Temperature	3000-6500K
CRI	>80
LED Life with L70 Criteria	>50000 Hours
Optics	Closed, Diffused
Efficacy	> 110 Lm/Watt

### General Parameters

Operating Temperature	-5 to 50 degree centigrade
Housing	Aluminium/Polycarbonate with Milky Diffuser
Finish	White
Off State Power	Zero
Certification	CE
Environment	IP-20



## PRODUCT ORDERING INFORMATION

Product Code	Product	CCT	Wattage
SH T8 9/18/20W CW/WW WH	LED Tube Light	Cool White/Warm White	09W-2F 18W-4F 20W-4F

Asia Pacific • Africa • Middle East • Europe  
Specifications are typical values and may change without notification.  
Copyright © Shaffer Energy. 2018 All rights reserved.