



< Benefits

- High Lumen Output
- Asthetically Designed
- Use of recycled and recyclable corrosion resistant materials.
- Full cutoff optics meet Dark Sky requirements
- Holistic Thermal Design:
- Underdriving LEDs to improve efficiency and system life.
- Use of premium grade alloys for enhanced thermal conduction.
- Electronics are isolated and sealed from the optical chamber.
- Surface & Pendent Mounting

Typical Applications Include:

- Industries
- Campuses
- Warehouse
- Shed & Yards

< Features

Electrical Parameters	
Input Voltage	140-270V AC
Wattage	80 to 150 Watt
Driver Efficiency	>90
Surge Protection	Up to 4KV
Power Factor	>0.9
Total Harmonic Distortion	<10
Over Voltage Protection	Provided
Optical Parameters	
Colour Temperature	5500-6500K
CRI	>70
LED Life with L70 Criteria	>50000 Hours
Efficacy	>110 Lumen per watt
Optics	High quality lens
Beam Angle	Flood, Wide
General Parameters	
Housing	Pressure Die Cast Aluminium
Operating Temperature Range	-10 to 50 degree centigrade
Off State Power	Zero
Certification	CE/RoHS
Finish	Black/Grey
Environment	IP-66



PRODUCT ORDERING INFORMATION

Product Code	Product	CCT	Wattage
SH UFO 80/100/120/150W CW	LED UFO Highbay	Cool White	80W 100W 120W 150W

Asia Pacific • Africa • Middle East • Europe
Specifications are typical values and may change without notification.
Copyright © Shaffer Energy. 2018 All rights reserved.