



Benefits

- Up to three unique beam distributions for application flexibility.
- Suitable for wet locations.
- Maintenance free operation, lasts up to 16 times longer than incandescent lighting.
- Superior thermal management allows for usage in recessed luminaires.
- Centralized optical package provides high quality point source beam versus pixelated designs.
- RoHS compliant – contains no mercury or lead.

Typical Applications Include:

- Fascia Board
- Cove Lighting
- Wall Washer

>Features

Electrical Parameters

Input Voltage	120-270V AC
Wattage	18W 36W 54W
Size	2 Feet 4 Feet
Power Factor	>0.95
Driver	Integrated/External
Protections	Over Voltage Short Circuit

Optical Parameters

Colour Temperature	WW/CW/RGB
CRI	>80
LEDs	High Power LED
LED Life with L70 Criteria	>50000Hours
Optics	High Quality Lens
Beam Angle	Narrow/Flood

General Parameters

Housing	Pressure Die Cast Aluminum
Operating Temperature Range	-20 to 50 degree centi-grade
Certification	CE
Environment	IP-65/IP-67



PRODUCT ORDERING INFORMATION

Product Code	Product	CCT	Wattage
SH WG 18/36/54W CW/WW 2F/4F BLK/SL	LED Wall Washer	Cool White/Warm White	18W 36W 54W

Asia Pacific • Africa • Middle East • Europe
Specifications are typical values and may change without notification.
Copyright © Shaffer Energy. 2018 All rights reserved.