



## < Benefits

- Sustainable and Aesthetically Designed.
- Suitable replacement of Halogen Zoom Light
- Works as excellent accent light with uniform beam control
- Available in Cool White, Warm White and Neutral White Color suitable for various requirement
- Appropriate Unify Glare Ratio.
- Use of premium grade alloys for enhanced thermal conduction.
- It has a 360° pitch and a 45° yaw allowing it to be easily adjusted and pointed in the direction required

### Typical Applications Include:

- Track Light
- Galleries
- Common Area Lighting.
- Showrooms

## < Features

### Electrical Parameters

Input Voltage	140-270V AC
Wattage	10W 16W 20W 24W 30W
Driver Efficiency	>90
Power Factor	>0.95
Total Harmonic Distortion	<10
Over Voltage Protection	Provided

### Optical Parameters

Colour Temperature	3000-6500K
CRI	>80
LED Life with L70 Criteria	>50000 Hours
Optics	High Quality Reflector
Efficacy	>100 Lm/Watt

### General Parameters

Housing	Pressure Die Cast Aluminium
Operating Temperature Range	-10 to 50 degree centi-grade
Mounting	Recessed
Tilt Angle	Upto 45 Degrees
Off State Power	Zero
Certification	CE
Environment	IP-20



## PRODUCT ORDERING INFORMATION

Product Code	Product	CCT	Wattage
SH ZL 10/16/20/24/30W CW/WW REC WH	LED Zoom Light	Cool White/Warm White	10W 16W 20W 24W 30W

Asia Pacific • Africa • Middle East • Europe  
Specifications are typical values and may change without notification.  
Copyright © Shaffer Energy. 2018 All rights reserved.